



15A 20A DESIGN: BALL TYPE

25A DESIGN: PTFE DISC TYPE

**Options:** Lever can be removed use with FA222 organ whistle

■ **Pressures:** 1000 kPa

■ **Services:** Water • Oil • Gases • Air  
Steam temp to 180°C

**Dimensions**

Size mm	15	20	25			
L	58	65	102			
H	51	51	70			
B	32	32	48			
A	120	130	135			
Wt/kgs	0.45	0.55	1.25			

11	STEM – PISTON	STAINLESS STEEL	ASTMA276 AISI316
10	BALL DISC	STAINLESS STEEL	AISI302
9	SPINDLE	DR BRASS	AISI567 -352
8	PIN CLEVIS	STEEL	
7	GLAND PACKING	PTFE GPI BUSH	AS1198
6	ARM-LEVER	GUNMETAL BRONZE	AS1565 C83600(m)
5	SPRING	STAINLESS STEEL	JIS4313 GR304
4	GLAND FOLLOWER	DR BRASS	AISI567 -352
3	VALVE – DISC PTFE	DR BRASS	AISI567 -352
2	END CAP	DR BRASS	AISI567 -352
1	BODY	GUNMETAL BRONZE	AS1565 C83600(m)
ITEM	DESCRIPTION	MAT'L	STANDARD



**Braemar Valves Pty Ltd**  
ABN 93 099 537 357  
5 Harley Crescent  
Condell Park NSW 2200

FIG No  
**FA240**

**BRONZE 'WHISTLE'**  
**RELIEF VALVE**

The detail contained in this sketch/drawing is the property of Braemar Valves Pty Ltd and cannot be copied or reprinted without permission from Braemar Valves Pty Ltd or their agents.

DRAWN	RJK	25.1.99	DRAWING NO.
			<b>103050-52</b>
SCALE	/	NTS	