



(A) Material Changes to 'DR BRASS'  
AS1567-351 on sizes 15mm & 20mm

**Dimensions**

Size mm	8	10	15	20	25	32	40	50	65	80	100
L	•	•	70	72	80	117	120	141	182	205	285
H	•	•	44	51	54	72	82	86	120	126	160
D	•	•	•	•	•	•	•	•	•	•	•
Wt/kgs	•	•	0.35	0.5	0.8	2.0	2.1	2.8	6.5	8.0	19.5

■ **Pressures:** 2100 kPa CWP  
Steam: 1200 kPa @ 200°C

■ **Standards:** Dezincification Resistant  
AS 1628 – 1994: Copper Alloy Valves  
AS 3855: Materials suitable for Potable Water Service

ITEM	DESCRIPTION	MAT'L	STANDARD
7	SPINDLE NUT	DR BRASS	AS1567-352
6	SPINDLE – PIN	STAINLESS STEEL	ASTM A276 94A AISI316
5	DISC NUT	DR BRASS	AS1567-352
4	DISC – FLAP (A)	GUNMETAL BRONZE	AS1565 C83600M
3	ARM (A)	GUNMETAL BRONZE	AS1565 C83600M
2	CAP – BONNET	GUNMETAL BRONZE	AS1565 C83600M
1	BODY	GUNMETAL BRONZE	AS1565 C83600M

ITEM	DESCRIPTION	MAT'L	STANDARD
------	-------------	-------	----------



**Braemar Valves Pty Ltd**  
ABN 93 099 537 357  
5 Harley Crescent  
Condell Park NSW 2200

FIG No **T4B** **BRONZE SWING CHECK VALVE SCREWED** CLASS 21 PN 20

DRAWN	RJK	11.5.98	DRAWING NO.
SCALE	/	NTS	<b>11750-58</b>

The detail contained in this sketch/drawing is the property of Braemar Valves Pty Ltd and cannot be copied or reprinted without permission from Braemar Valves Pty Ltd or their agents.

FORM# 1297/1